



CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO

GIA BAO INTERNATIONAL INVESTMENT MTV COMPANY LIMITED

- Địa chỉ: B4/112/5 Ấp 4, Đa Phước, Bình Chánh, HCM.

- Showroom: 233 Phạm Thế Hiển, Phường 3, Quận 8, HCM.

- Mobile: 0909717982

- Email: Info@giabao.net.vn

TP.HCM, Ngày 20 tháng 05 năm 2024.

BẢNG BÁO GIÁ

Theo yêu cầu của Quý Công Ty, Chúng tôi xin phép được báo giá như sau:

SẢN PHẨM	THÔNG SỐ KỸ THUẬT	ĐVT	SL	ĐƠN GIÁ (VND) (bao gồm 10%VAT)
 ĐỒNG HỒ ĐO LỰC ĐIỆN TỬ CHECKLINE M7-100	Model: M7-100 Tồn kho: 79 - LbF/ozF/kgF/gF/N: 100.00-000.02/1600.0-0 000.5/50.00-00.01/50000.0-10.0/500.0-000. 1. - Sampling Rate: 14,000 Hz - Accuracy: $\pm 0.1\%$ of Full Scale - Power: AC or rechargeable battery. Multi- step low battery indicator is displayed, gauge shuts off automatically when power is too low. - Battery Life: Backlight on: up to 7 hours of continuous use Backlight off: up to 24 hours of continuous use - Measurement Units: lbF, ozF, gF, kgF, N, kN, mN (depending on model) - Outputs: USB / RS-232: Fully configurable up to 115,200 baud. Includes Gauge Control Language 2 for full computer control. Mitutoyo (Digimatic): Serial BCD suitable for all Mitutoyo SPC-compatible devices. Analog: ± 1 V DC, $\pm 0.25\%$ of full scale at capacity. General Purpose: Three open drain outputs, one input. Set Points: Three open drain lines. - Configurable settings: Digital filters, outputs, automatic output (via USB/RS-232), automatic shutoff, default settings, averaging mode, external trigger, passwords, key tones, audio alarms,	Cái	1	Liên hệ

	backlight, calibration - Safe Overload: 150% of full scale (display shows "OVLD" at 110% and above) - Load cell deflection: All models 0.010" [0.25mm], except 0.005" [0.13mm] for M7-012 - Operating Temperature Range: 40 - 100°F, max. 96% humidity, non-condensating - Weight(gauge only): M7-012 - M7-100: 1.0 lb [0.45 kg] M7-200 - M7-500: 1.2 lb [0.54 kg] - Included Accessories: Carrying case with chisel, cone, V-groove, hook, flat, extension rod, universal voltage AC adapter, battery, quick-start guide, USB cable, resource CD (USB driver, MESURTMLite software, MESURTMgauge DEMO software, and user's guide), and NIST-traceable certificate of calibration with data. - Hãng: Checkline - Xuất xứ: US			
--	---	--	--	--

- Thanh toán: Tiền mặt / Chuyển khoản.

Tài Khoản Công Ty

CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO
STK: 018 100 354 9161
Ngân hàng VCB - CN Nam Sài Gòn

Tài Khoản Cá Nhân

Tên chủ TK: Nguyễn Thị Trang Châu
Số Tk: 033 100 372 0472
Ngân hàng: VCB CN Bến Thành

- Ngày giao hàng: Thỏa thuận.

- Nơi giao: Quận 8 ± 7Km.

- Bảo hành: Tại Văn Phòng Gia Bảo, BH kỹ thuật (motor), không bảo hành phụ kiện: Đầu đo, đế từ, mài mòn...

XÁC NHẬN ĐƠN HÀNG

(Ký tên & Đóng dấu)

CÔNG TY GIA BẢO

(GIÁM ĐỐC)