



CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO

GIA BAO INTERNATIONAL INVESTMENT MTV COMPANY LIMITED

- Địa chỉ: B4/112/5 Ấp 4, Đa Phước, Bình Chánh, HCM.
- Showroom: 233 Phạm Thế Hiển, Phường 3, Quận 8, HCM.
- Mobile: 0909717982 - Email: Info@giabao.net.vn

TP.HCM, Ngày 20 tháng 05 năm 2024.

BẢNG BÁO GIÁ

Theo yêu cầu của Quý Công Ty, Chúng tôi xin phép được báo giá như sau:

SẢN PHẨM	THÔNG SỐ KỸ THUẬT	ĐVT	SL	ĐƠN GIÁ (VND) (bao gồm 10%VAT)
 ĐỒNG HỒ ĐO LỰC ĐIỆN TỬ CHECKLINE FGV-2XY	Model: FGV-2XY Tồn kho: 79 -Capacity: 2 lb / 10 N / 1000 g / 32 oz. - Measuring Modes: Realtime, Compression Peak, Tension Peak - Display Update Rate: User Selectable: 1, 2, 3, 5, 10, 20 times per second - Sampling Rate: 1000 times per second (1000Hz/1KHz) - Accuracy: $\pm 0.2\%$ F.S. - Temperature DriftGain : $\pm 0.01\%$ LOAD / Zero : $\pm 0.01\%$ / R.C. / Drift of zero point can be cancelled with tracking function. - Display: Main display: 4-digits 12mm high, Reversible Units display: 3-digits 7mm high Other display: "LO BAT"(Low Battery Voltage), "BAT"(Battery Charging), "OVR"(Overload), "Peak"(Peak Hold) - Overload: 200% of Full Scale - On Model FGV-200XY: 150% F.S. - Tracking: User Selectable (ON/OFF) - USB Output: Allows communication between FGV-XY and Windows PC Software with ToriemonUSB via USB cable(included). - RS-232C Output: Allows communication between the FGV-XY and RS-232C devices. RS-232C cable is an optional accessory. - Analog Output: $\pm 1V$, Accuracy is $\pm 50mV$ through a 12 bit D/A. ZERO affects this output, and is updated at 1000 times/second. Load is $>10k$ Ohms - Overload/Comparator Output: Open-	Cái	1	Liên hệ

	collector output (Max DC30V/5mA). - Power: Rechargeable Nickel hydride battery or AC adapter/charger. Usable while charging. - Operating Time: Approximately 8 hours after a full charge. Charging Time: 16 Hours Max. - Auto Power Off: Default is 10 minutes. Can be disabled. Automatically disabled when connected to AC adapter. - Memory function: Continuous memory: 1000 data points, Single memory: 100 data points, Standard memory: 50 data points - Statistics functions (max, minimum, peak, average, standard deviation) - Comparator function: User Selectable: HI and LO - Temperature range: 0 ~ 40 °C (32 ~ 104 °F) - Humidity range: 35 ~ 85% RH - Dimensions: 147mm (L)x 75mm (W) x 38mm(H) - Weight: Approx. 450g - On Model FGV-200XY: Approx. 500g - Accessories: (Included)AC adapter/charger, carrying case, hook, chisel, flat head, notched head, hanger, cone head, thread Adapter, extension rod, USB cable - Toriemon Software: for WIN 7 & 2000 (64 bit) and XP (32 bit), and is meant for use with Office/Excel 2000 and higher - Hãng: Checkline - Xuất xứ: US			
--	--	--	--	--

- Thanh toán: Tiền mặt / Chuyển khoản.

Tài Khoản Công Ty

CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO
 STK: 018 100 354 9161
 Ngân hàng VCB - CN Nam Sài Gòn

Tài Khoản Cá Nhân

Tên chủ TK: Nguyễn Thị Trang Châu
 Số Tk: 033 100 372 0472
 Ngân hàng: VCB CN Bến Thành

- Ngày giao hàng: Thỏa thuận.

- Nơi giao: Quận 8 ± 7Km.

- Bảo hành: Tại Văn Phòng Gia Bảo, BH kỹ thuật (motor), không bảo hành phụ kiện: Đầu đo, đế từ, mài mòn...

XÁC NHẬN ĐƠN HÀNG
 (Ký tên & Đóng dấu)

CÔNG TY GIA BẢO
 (GIÁM ĐỐC)