



CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO

GIA BAO INTERNATIONAL INVESTMENT MTV COMPANY LIMITED

- Địa chỉ: B4/112/5 Ấp 4, Đa Phước, Bình Chánh, HCM.

- Showroom: 233 Phạm Thế Hiển, Phường 3, Quận 8, HCM.

- Mobile: 0909717982

- Email: Info@giabao.net.vn

TP.HCM, Ngày 12 tháng 05 năm 2025.

BẢNG BÁO GIÁ

Theo yêu cầu của Quý Công Ty, Chúng tôi xin phép được báo giá như sau:

SẢN PHẨM	THÔNG SỐ KỸ THUẬT	ĐVT	SL	ĐƠN GIÁ (VND) (bao gồm 10%VAT)
 SIÊU ÂM CHIỀU DÀY VẬT LIỆU CHECKLINE ZX-5	Model: ZX-5 Tồn kho: 79 - Total Measuring Range (Steel): 0.025 - 36.000 inches 0.63 - 914.4 mm (depends on material and transducer/probe type) - Measuring Range (Steel): 0.040-8.000 inches 1.00-199.9 mm (with standard transducer T-102-2000) - Resolution: 0.001 inch (0.01 mm) - Velocity Range: 0.0120 to .7300 in/μs. 305 to 18,542 meters/sec - LCD Display: Multi-function 7 segment 4.5 digit liquid crystal display with 0.500" digit height. Two 0.125 in14 segment fields for labels and values, and one 7 segment field for labels and values. Additional icons to indicate features and modes - Display Backlight: Backlight is selectable on/off/auto, and selectable brightness (Lo, Med, Hi) options - Display Update Rate: 10 Hz (10 updates/sec) - Probe (Standard): 1/4", 5 MHz Dual Element Transducer, actual wearface is 5/8" (17mm), p/n T-102-3300 - Probes (optional): 1 to 10 MHz, 3/16" up to 1 inch (custom probes available) - Probe Wearface: PEEK (Polyethylethylkytone) - Cable: 1.2m (4ft.) waterproof cable with	Cái	1	Liên hệ

	non-polarized, quick-disconnect connectors - Temp. Limits: Ambient: -30 to 75° C (-22 to 167° F) - Material: -20 to 100° C (0 to 200° F) - High temperature probes available - Battery Type: 2x AA batteries (rechargeable batteries can be used) - Battery Life: 45 hours continuous use - Weight: 308 grams (11 ounces) - Dimensions: 63.5 x 131.3 x 31.5 mm (2.5" x 5.17" x 1.25") - Accessories: Probe/cable assembly, 4 oz. bottle of coupling fluid, NIST Calibration Certificate, 2 AA batteries, operating instructions, hard-plastic carrying case. - Housing: Extruded aluminum body with nickel-plated aluminum end caps (gasket sealed) - Housing Rating: IP65 - Certifications: NIST Traceable and MIL-STD-45662A - Keypad: Sealed membrane that is resistant to both water and petroleum products - Seven or eight tactile-feedback keys - Pulse Repetition Frequency (PRF): 200 Hz (200 pulses/sec) - To Lock Settings: With gauge powered off, press and hold the "+" key while powering on the gauge - The LOCK icon will be illuminated on the Display - To unLock Settings: With gauge powered off, press and hold the "-" key while powering on the gauge - The LOCK icon will turn off - GAIN Adjustment: Adjustable GAIN 5-position (VLOW, LOW, MED, HIGH, VHI), in 3dB steps, 40-52dB - Measuring Modes: Pulse-Echo (P-E), Differential - Output Type: USB-C (single data value transfer, no built-in memory) - Hãng: Checkline - Xuất xứ: US			
--	---	--	--	--

- Thanh toán: Tiền mặt / Chuyển khoản.

Tài Khoản Công Ty

CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO
 STK: 018 100 354 9161
 Ngân hàng VCB - CN Nam Sài Gòn

Tài Khoản Cá Nhân

Tên chủ TK: Nguyễn Thị Trang Châu
 Số Tk: 033 100 372 0472
 Ngân hàng: VCB CN Bến Thành

- Ngày giao hàng: Thỏa thuận.

-
- Nơi giao: Quận 8 $\pm$ 7Km.
 - Bảo hành: Tại Văn Phòng Gia Bảo, BH kỹ thuật (motor), không bảo hành phụ kiện: Đầu đo, đế từ, mài mòn...

XÁC NHẬN ĐƠN HÀNG
(Ký tên & Đóng dấu)

CÔNG TY GIA BẢO
(GIÁM ĐỐC)