



CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO


GIA BAO INTERNATIONAL INVESTMENT MTV COMPANY LIMITED

- Địa chỉ: D4/112/5 Ấp 4, Xã Hưng Long, TP Hồ Chí Minh, Việt Nam.
- Showroom: 133 Đào Cam Mộc, Phường Chánh Hưng, TP Hồ Chí Minh.
- Mobile: **0909717982** - Email: Info@giabao.net.vn

TP.HCM, Ngày 01 tháng 07 năm 2026.

BẢNG BÁO GIÁ

Theo yêu cầu của Quý Công Ty, Chúng tôi xin phép được báo giá như sau:

SẢN PHẨM	THÔNG SỐ KỸ THUẬT	ĐVT	SL	ĐƠN GIÁ (VND) (bao gồm % VAT)
 <p>SIÊU ÂM CHIỀU DÀY VẬT LIỆU CHECKLINE ZX-6</p>	<p>Model: ZX-6</p> <p>Tồn kho: 79</p> <ul style="list-style-type: none">- Range in Steel: Pulse-Echo Mode (Pit & Flaw Detection) measures from 0.025 to 19.999 inches (0.63 to 500 millimeters)Echo-Echo Mode (Through Paint & Coatings) measures from 0.100 to 1.000 inch (2.54 to 25.40 millimeters)(range depends upon probe selected) - five probes to choose from- Resolution: 0.001 inch (0.01 mm)- Velocity Range: 0.0120 to .7300 in/μs. 305 to 18,542 meters/sec- Probe (Standard): 1/4", 5 MHz Hi-Damp Dual Element Transducer, actual wearface is 5/8" (17mm), p/n T-102-2700- Probes (optional): 1 to 10 MHz, 3/16" up to 1 inch (custom probes available)- Probe Wearface: PEEK (Polyethylethylkytone)- Cable: 1.2m (4ft.) waterproof cable with non-polarized, quick-disconnect connectors- LCD Display: Multi-function 7 segment 4.5 digit liquid crystal display with 0.500" digit height. Two 0.125 in14 segment fields for labels and values, and one 7 segment field for labels and values. Additional icons to indicate features and modes- Display Backlight: Backlight is selectable on/off/auto, and selectable brightness (Lo, Med, Hi) options- Display Update Rate: 10 Hz (10 updates/sec)	Cái	1	Liên hệ

- Temp. Limits: Ambient: -30 to 75° C (-22 to 167° F)
 Material: -20 to 100° C (0 to 200° F)
 High temperature probes available
 - Battery Type: 2x AA batteries (rechargeable batteries can be used)
 - Battery Life: 45 hours continuous use
 - Weight: 308 grams (11 ounces)
 - Dimensions: 63.5 x 131.3 x 31.5 mm (2.5" x 5.17" x 1.25")
 - Accessories: Probe/cable assembly, 4 oz. bottle of coupling fluid, NIST Calibration Certificate, 2 AA batteries, operating instructions, hard-plastic carrying case.
 - Housing: Extruded aluminum body with nickel-plated aluminum end caps (gasket sealed)
 - Housing Rating: IP65
 - Certifications: NIST Traceable and MIL-STD-45662A
 - Keypad: Sealed membrane that is resistant to both water and petroleum products
 Seven or eight tactile-feedback keys
 - Pulse Repetition Frequency (PRF): 200 Hz (200 pulses/sec)
 - To Lock Settings: With gauge powered off, press and hold the "+" key while powering on the gauge
 The LOCK icon will be illuminated on the Display
 - To unLock Settings: With gauge powered off, press and hold the "-" key while powering on the gauge
 The LOCK icon will turn off
 - GAIN Adjustment: Adjustable GAIN 5-position (VLOW, LOW, MED, HIGH, VHI), in 3dB steps, 40-52dB
 - Measuring Mode: Pulse-Echo (P-E), Echo-Echo (E-E, Thru-Paint Mode), Scan, Differential, Alarm and VX-velocity
 - Time Dependent Gain (TDG): Used in both pulse-echo (P-E) and Echo-Echo (E-E) modes depending on transducer and frequency selected
 - Pulser: 150 volt square wave pulser
 - Hãng: Checkline
 - Xuất xứ: US

- Thanh toán: Tiền mặt / Chuyển khoản.

Tài Khoản Công Ty

CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO
 STK: 018 100 354 9161

Tài Khoản Cá Nhân

Tên chủ TK: Nguyễn Thị Trang Châu
 Số Tk: 033 100 372 0472

Ngân hàng VCB - CN Nam Sài Gòn

Ngân hàng: VCB CN Bến Thành

- Ngày giao hàng: Thỏa thuận.

- Nơi giao: Quận 8 ± 7Km.

- Bảo hành: Tại Văn Phòng Gia Bảo, BH kỹ thuật (motor), không bảo hành phụ kiện: Đầu đo, đế từ, mài mòn...

XÁC NHẬN ĐƠN HÀNG
(Ký tên & Đóng dấu)

CÔNG TY GIA BẢO
(GIÁM ĐỐC)