



## CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO

GIA BAO INTERNATIONAL INVESTMENT MTV COMPANY LIMITED

- Địa chỉ: D4/112/5 Ấp 4, Xã Hưng Long, TP Hồ Chí Minh, Việt Nam.
- Showroom: 133 Đào Cam Mộc, Phường Chánh Hưng, TP Hồ Chí Minh.
- Mobile: **0909717982** - Email: [Info@giabao.net.vn](mailto:Info@giabao.net.vn)

TP.HCM, Ngày 01 tháng 07 năm 2026.

# BẢNG BÁO GIÁ

Theo yêu cầu của Quý Công Ty, Chúng tôi xin phép được báo giá như sau:

SẢN PHẨM	THÔNG SỐ KỸ THUẬT	ĐVT	SL	ĐƠN GIÁ (VND) (bao gồm % VAT)
 <p><b>SIÊU ÂM CHIỀU DÀY VẬT LIỆU CHECKLINE ZX-6DL</b></p>	<p>Model: <b>ZX-6DL</b></p> <p>Tồn kho: <b>79</b></p> <p>Range in Steel: Pulse-Echo Mode (Pit &amp; Flaw Detection) measures from 0.025 to 19.999 inches(0.63 to 500 millimeters) Echo-Echo Mode (Through Paint &amp; Coatings) measures from 0.100 to 1.000 inch (2.54 to 25.40 millimeters) (range depends upon probe selected) - five probes to choose from Resolution: 0.001 inch (0.01 mm) Velocity Range: 0.0120 to .7300 in/<math>\mu</math>s. 305 to 18,542 meters/sec LCD Display: Multi-function 7 segment 4.5 digit liquid crystal display with 0.500" digit height. Two 0.125 in14 segment fields for labels and values, and one 7 segment field for labels and values. Additional icons to indicate features and modes Display Backlight: Backlight is selectable on/off/auto, and selectable brightness (Lo, Med, Hi) options Display Update Rate: 10 Hz (10 updates/sec) Probes (optional):1 to 10 MHz, 3/16" up to 1 inch (custom probes available) Probe (Standard): 1/4", 5 MHz Hi-Damp Dual Element Transducer, actual wearface is 5/8" (17mm), p/n T-102-2700 Probe Wearface: PEEK (Polyethylethylkytone) Cable: 1.2m (4ft.) waterproof cable with non-polarized, quick-disconnect connectors</p>	Cái	1	Liên hệ

	<p>Temp. Limits:  Ambient: -30 to 75° C (-22 to 167° F)  Material: -20 to 100° C (0 to 200° F)  High temperature probes available  Battery Type: 2x AA batteries (rechargeable batteries can be used)  Battery Life: 45 hours continuous use  Weight: 308 grams (11 ounces)  Dimensions 63.5 x 131.3 x 31.5 mm (2.5" x 5.17" x 1.25")  Accessories Probe/cable assembly, 4 oz. bottle of coupling fluid, NIST Calibration Certificate, 2 AA batteries, operating instructions, hard-plastic carrying case.  Housing Extruded aluminum body with nickel-plated aluminum end caps (gasket sealed)  Housing Rating IP65  Certifications NIST Traceable and MIL-STD-45662A  Keypad Sealed membrane that is resistant to both water and petroleum products  Seven or eight tactile-feedback keys  Pulse Repetition Frequency (PRF) 200 Hz (200 pulses/sec)  To Lock Settings With gauge powered off, press and hold the "+" key while powering on the gauge  The LOCK icon will be illuminated on the Display  To unLock Settings With gauge powered off, press and hold the "-" key while powering on the gauge  The LOCK icon will turn off  GAIN Adjustment Adjustable GAIN 5-position (VLOW, LOW, MED, HIGH, VHI), in 3dB steps, 40-52dB  Measuring Mode Pulse-Echo (P-E), Echo-Echo (E-E, Thru-Paint Mode), Scan, Differential, Alarm and VX-velocity  Output Type USB-C (plug-n-play, view files on PC which can be dragged and dropped)  Built-In Memory 10,000 data values stored in up to 40 batches with 250 values/batch  Memory Type Sequential data file (single column)  - Hãng: Checkline  - Xuất xứ: US.</p>			
--	---	--	--	--

- Thanh toán: Tiền mặt / Chuyển khoản.

**Tài Khoản Công Ty**

CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO  
STK: 018 100 354 9161

**Tài Khoản Cá Nhân**

Tên chủ TK: Nguyễn Thị Trang Châu  
Số Tk: 033 100 372 0472

---

Ngân hàng VCB - CN Nam Sài Gòn

Ngân hàng: VCB CN Bến Thành

- Ngày giao hàng: Thỏa thuận.

- Nơi giao: Quận 8 ± 7Km.

- Bảo hành: Tại Văn Phòng Gia Bảo, BH kỹ thuật ( motor), không bảo hành phụ kiện: Đầu đo, đế từ, mài mòn...

**XÁC NHẬN ĐƠN HÀNG**  
(Ký tên & Đóng dấu)

**CÔNG TY GIA BẢO**  
( GIÁM ĐỐC)