



CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO

GIA BAO INTERNATIONAL INVESTMENT MTV COMPANY LIMITED

- Địa chỉ: B4/112/5 Ấp 4, Đa Phước, Bình Chánh, HCM.

- Showroom: 233 Phạm Thế Hiển, Phường 3, Quận 8, HCM.

- Mobile: 0909717982

- Email: Info@giabao.net.vn

TP.HCM, Ngày 06 tháng 05 năm 2024.

BẢNG BÁO GIÁ

Theo yêu cầu của Quý Công Ty, Chúng tôi xin phép được báo giá như sau:

SẢN PHẨM	THÔNG SỐ KỸ THUẬT	ĐVT	SL	ĐƠN GIÁ (VND) (bao gồm 10%VAT)
 ĐO ĐỘ DÀY LỚP PHỦ CHECKLINE MiniTest 745	Model: MiniTest 745 Tồn kho: 79 - Sensor Type: Convertible from external to built-in sensor - Measuring Ranges: Up to 15 mm - Substrate Identification: Yes, with FN sensors - SIDSP® sensor: Yes, for increased accuracy and reproducibility - Sensor characteristics: High-accuracy sensor characteristics through up to 50 calibration points during the sensor manufacture - Individual temperature compensation: Yes - Number of memories: 100, user-definable memory arrangement according to batches - Total memory capacity: max. 100,000 - Memory batches: Include readings, a defined calibration mode, parameters and statistics calculated from batch readings - Statistical evaluation: Number of readings, minimum, maximum, mean value, standard deviation, coefficient of variation - Single reading statistics: Block value statistics (norm-conforming/ user-configurable), stored readings and statistical values can be called seperately, print-out readings and statistics on MiniPrint 7000 data printer, transfer of readings and statistics to a PC - Calibration modes: Factory calibration, zero-point, 2-points, 3-point calibration, calibration method "rough", user-adjustable	Cái	1	Liên hệ

	off-set value, user-adjustable correction value for substrate roughness - International calibration procedures: ISO, SSPC, "Swedish", "Australian" - Measuring units: metric (μm , mm, cm) / imperial (mils, inch, thou) switchable - Display: Large graphical display, backlit, 180° rotatable - Menu: User-friendly, 25 languages - Software: Sensor and gauge software updates available via download - Measuring rate/ accuracy: User adjustable to standard, quick, high precision - Thickness identification: Continuous mode for quick identification of changes in thickness - Automatic switch-off: Battery saving mode with adjustable switch-off mode - Protection: IP40 - Operating temperature: -10°C - 60°C - Storage temperature: - 20°C - 70°C - Data interfaces: Bluetooth® 4.0, Bluetooth Smart®, Mini-USB - Power supply: 2 x AA (Mignon cells), rechargeable NiMH accu batteries type AA/HR6 (as an option) - Norms and standards: DIN EN ISO 1461, 2064, 2178, 2360, 2808, 3882, 19840, ASTM B 244, B 499, D7091, E 376, AS 3894.3, SS 1841 60, SSPC-PA 2 - Dimensions: 157 mm x 75,5 mm x 49 mm - Weight: approx. 175 g - Hãng: Checkline - Xuất xứ: USA			
--	--	--	--	--

- Thanh toán: Tiền mặt / Chuyển khoản.

Tài Khoản Công Ty

CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO
 STK: 018 100 354 9161
 Ngân hàng VCB - CN Nam Sài Gòn

Tài Khoản Cá Nhân

Tên chủ TK: Nguyễn Thị Trang Châu
 Số Tk: 033 100 372 0472
 Ngân hàng: VCB CN Bến Thành

- Ngày giao hàng: Thỏa thuận.

- Nơi giao: Quận 8 $\pm$ 7Km.

- Bảo hành: Tại Văn Phòng Gia Bảo, BH kỹ thuật (motor), không bảo hành phụ kiện: Đầu đo, đế từ, mài mòn...

XÁC NHẬN ĐƠN HÀNG
 (Ký tên & Đóng dấu)

CÔNG TY GIA BẢO
 (GIÁM ĐỐC)