



CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO

GIA BAO INTERNATIONAL INVESTMENT MTV COMPANY LIMITED

- Địa chỉ: D4/112/5 Ấp 4, Xã Hưng Long, TP Hồ Chí Minh, Việt Nam.
- Showroom: 133 Đào Cam Mộc, Phường Chánh Hưng, TP Hồ Chí Minh.
- Mobile: 0909717982 - Email: Info@giabao.net.vn

TP.HCM, Ngày 17 tháng 12 năm 2025.

BẢNG BÁO GIÁ

Theo yêu cầu của Quý Công Ty, Chúng tôi xin phép được báo giá như sau:

SẢN PHẨM	THÔNG SỐ KỸ THUẬT	ĐVT	SL	ĐƠN GIÁ (VND) (bao gồm % VAT)
 ĐỒNG HỒ VẠN NĂNG KYORITSU K-1062	Model: K-1062 Tồn kho: 79 -Detection mode: MEAN/RMS (switch) -DC V: 50.000/500.00/2400.0mV/5.0000/50.000/500.00/1000.0V (Input impedance: Approx. 100MΩ [50/500/2400mV], 10MΩ [5/50/500/1000V]) ±0.02%rdg±2dgt (Basic accuracy) -AC V [RMS]: 50.000/500.00mV/5.0000/50.000/500.00/1000.0V (Input impedance: 11MΩ<50pF [50/500mV/5V], 10MΩ<50pF [50/500/1000V]) ±0.4%rdg±30dgt (Basic accuracy) -AC V [MEAN]: 50.000/500.00mV/5.0000/50.000/500.00/1000.0V (Input impedance: 11MΩ<50pF [50/500mV/5V], 10MΩ<50pF [50/500/1000V]) ±1%rdg±30dgt (Basic accuracy) -DCV+ACV: 5.0000/50.000/500.00/1000.0V (Input impedance: 11MΩ<50pF [5V], 10MΩ<50pF [50/500/1000V]) ±0.5%rdg±10dgt (Basic accuracy) -DC A: 500.00/5000.0μA/50.000/500.00mA/5.0000/10.000A ±0.2%rdg±5dgt (Basic accuracy)	Cái	1	12.255.000 VNĐ

-AC A [RMS]: 500.00/5000.0μA/50.000/500.00mA/5.0000/10.000A
±0.75%rdg±20dgt (Basic accuracy)

-AC A [MEAN]:
500.00/5000.0μA/50.000/500.00mA/5.0000/10.000A
±1.5%rdg±20dgt (Basic accuracy)

-DCA+ACA: 500.00/5000.0μA/50.000/500.00mA/5.0000/10.000A
±1%rdg±10dgt (Basic accuracy)

-Ω: 500.00Ω/5.0000/50.000/500.00kΩ/5.0000/50.000MΩ
±0.05%rdg±2dgt (Basic accuracy)

-LowPower-Ω:
5.000/50.00/500.0kΩ/5.000MΩ
±0.2%rdg±3dgt (Basic accuracy)

-Continuity buzzer: 500.0Ω (The buzzer turns on for resistances lower than 100±50Ω)

-Diode test: 2.4000V ±1%rdg±2dgt
Open circuit voltage: <5V (Approx. 0.5mA Measuring Current)

-Capacitance: 5.000/50.00/500.0nF/5.000/50.00/500.0μF/5.000/50.00mF
±1%rdg±5dgt (Basic accuracy)

-Frequency: 2.000 - 9.999/9.00 - 99.99/90.0 - 999.9Hz/0.900 - 9.999/9.00 - 99.99kHz
±0.02%rdg±1dgt (Basic accuracy)

-DUTY: 10 - 90% ±1%rdg

-Temperature: -200 - 1372°C
±1%rdg±1.5°C
-328 - 2501.6°F ±1%rdg±2.0°F
(with the use of K-type Temperature probe)

-Measurement functions: DC Voltage, AC Voltage, DC Current, AC Current, Resistance, Frequency, Temperature, Capacitor, Duty cycle ratio, Decibel (dBV, dBm), Continuity Check, Diode Test, LowPower-Ω

-Other functions: Data Hold (D/H), Auto Hold (A/H), Peak Hold (P/H), Range Hold (R/H), Maximum value (MAX), Minimum value (MIN), Average value (AVG), Zero

	Adjustment (Capacitor, Resistance), Relative values, Save to Memory, LCD backlight -Applicable standards: IEC 61010-1 CAT IV 600V, CAT III 1000V Pollution degree 2, IEC 61010-031, IEC 61326-1 (EMC) -Power source: R6 (1.5V)×4 (Auto power off: approx. 20 minutes) -Dimensions: 192(L)×90(W)×49(D) mm -Weight: Approx. 560g (including batteries) -Included Accessories: 7220A (Test leads), R6×4, Instruction manual, 8926 (Fuse [440mA/1000V])×1 (included) 8927 (Fuse [10A/1000V])×1 (included)			
--	--	--	--	--

- Thanh toán: Tiền mặt / Chuyển khoản.

Tài Khoản Công Ty

CÔNG TY TNHH MTV ĐẦU TƯ QUỐC TẾ GIA BẢO
STK: 018 100 354 9161
Ngân hàng VCB - CN Nam Sài Gòn

Tài Khoản Cá Nhân

Tên chủ TK: Nguyễn Thị Trang Châu
Số Tk: 033 100 372 0472
Ngân hàng: VCB CN Bến Thành

- Ngày giao hàng: Thỏa thuận.
- Nơi giao: Quận 8 ± 7Km.
- Bảo hành: Tại Văn Phòng Gia Bảo, BH kỹ thuật (motor), không bảo hành phụ kiện: Đầu đo, đế từ, mài mòn...

XÁC NHẬN ĐƠN HÀNG
(Ký tên & Đóng dấu)

CÔNG TY GIA BẢO
(GIÁM ĐỐC)